


DRY WALL ELECTRICAL INSTALLATION MATERIALS
MODUL SWITCH BOX
TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU		
Directives & Standards	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements		
Halogen Acid Gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014		
Applications	Internal - Residential - Industrial		
Installations	Plastic box for Installation – Multi Gang mechanisms Lighting Switches, Plug Sockets etc Knockout entries for Conduits, Cables – Max Ø20mm Flush mount – Dry / Hallow walls - Gypsum plasterboard		
Structural Material	Modified Thermoplastic Polyolefin		
Characteristics	IP Rate	3X	
	Glow Wire Test	850 °C	
	UV Resistance	LR	
	Chemicals Resistance	R	
	Dielectric strength	400V	
	Temperature Range	-15 °C	+60 °C
	Color	Yellow RAL 1021	



Switch Combinations



TYPE	MODULE	INSTALLATION
CODE	08-21046-003	
A / mm	65	
B / mm	110	
C / mm	50	
Packing / pcs	50	

