



SPIRAL DIN LIGHT TYPE 320N

TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU						
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems DIN 49018-1, Dimensions reference						
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS						
Applications	Indoor – Cable routing through masonry						
Installations	Residential and Industrial indoor installations Flush masonry mounting						
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Internally fits with as system with Rigid pipe COURLINE DIN E/T						
Structural material	Polyvinyl chloride (U-PVC)						
Classification EN 61386-1	2 2 2 1						
Compression resistance	2	Compression Force		320N / 5cm			
Impact Resistance	2	Mass	1.0 kg	Height	100mm		
Temperature Range	2	Lower Temperature		- 5 °C			
	1	Higher Temperature		+ 60 °C			
Bending Resistance	2	Pliable					
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance >100MΩ			
Color	Standard	White	Available	Blue	Yellow	Red	Green



TYPE:	11	13,5	16	23	29
CODE:	03-210 35-011	03-210 36-013	03-210 37-016	03-210 38-023	03-210 34-029
D₁ External Ø / mm	15,8	19	21,5	29	34,8
D₂ Internal Ø / mm	12,4	14,7	17	24,4	29,3
Packing – Coil / m	200	200	200	100	50

