




# CABLE TRUNKING

## ON-FLOOR INSTALLATIONS

### TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU		
Standards Amends	EN 50085-1:2005+A1:2013 - General requirements Cable Trunking / Ducting systems for electrical installations EN 50085-2-1:2006/A1:2011 Cable Trunking / Ducting systems for mounting on walls and ceilings		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications	Indoor - Residential - Commercial - Industrial Plastic rigid Trunking with Removable cover		
Installations	Exposed - OnFloor		
	Wiring, Power, Telecom, DATA, AUDIO, SAT, TV		
Material	Polyvinyl Chloride > U-PVC		
Characteristics	Glow Wire Test	800 °C	
	Resistance - UV	R	
	Resistance - Chemicals	R	
	Resistance - Fire	FR-SE	
	Temperature Range	-15 °C	+60 °C
	Color.1	White RAL9010	Color.2 Grey RAL7035



TYPE:	50x12G	50x12W	70x20G	70x20W
CODE:	24-200 30-121	24-200 31-161	24-200 32-201	24-200 33-251
Dimensions / mm:	50x12	50x12	70x20	70x20
Length (m)	2	2	2	2
Capacity Max Ø (1)	8	8	12	12
Capacity Max Ø (2)	6	6	10	10
Color	Grey	White	Grey	White
Packing / pcs:	50	50	24	24

