



CABLE TRUNKING

PLASTIC CABLE TRUNKING PLAIN

TECHNICAL DATA SHEET

| | | | | |
|------------------|---|-----------------|--------|-----|
| Directive | LVD 2014/35/EU | | | |
| Standards Amends | EN 50085-1:2005+A1:2013 - General requirements Cable Trunking /Ducting systems for electrical installations EN 50085-2-1:2006/A1:2011 Cable Trunking / Ducting systems intended for mounting on walls and ceilings | | | |
| RoHS Compliant | 2022/95/EC Restriction of Hazardous substances, RoHS | | | |
| Applications | Indoor – Outdoor - Residential – Industrial Plastic rigid Trunking with Removable cover and Installation Base punching | | | |
| Installations | Exposed – Wall mounted - OnFloor | | | |
| | Wiring, Power, Lighting, Telecom, CCTV, AUDIO, SAT, TV, FIBER | | | |
| Material | Polyvinyl Chloride > U-PVC | | | |
| Characteristics | Glow Wire Test | 800 °C | | |
| | Resistance - UV | R | | |
| | Resistance - Chemicals | R | | |
| | Resistance - Fire | FR-SE | | |
| | Temperature Range | -15 °C | +60 °C | |
| | Color | White – RAL9010 | Length | 2 m |



| | | | | | | | | | | | |
|----------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| TYPE: | 20x10 | 25x16 | 25x25 | 40x25 | 40x40 | 60x40 | 60x60 | 80x40 | 80x60 | 100x40 | 100x60 |
| CODE: | 24-200 15-201 | 24-200 16-251 | 24-200 01-252 | 24-200 17-402 | 24-200 02-404 | 24-200 14-604 | 24-200 03-606 | 24-200 04-804 | 24-200 05-806 | 24-200 06-100 | 24-200 07-106 |
| DIAMENTIONS A x B / mm: | 20x10 | 25x16 | 25x25 | 40x25 | 40x40 | 60x40 | 60x60 | 80x40 | 80x60 | 100x40 | 100x60 |
| PACKING / pcs: | 200 | 140 | 90 | 80 | 72 | 48 | 32 | 36 | 24 | 28 | 18 |

