
















# RIGID CONDUITS

## COMBO RIGID LIGHT TYPE 320N

### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU						
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems						
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS						
Applications Installations	Indoor – Cable routing Residential and Industrial indoor installations Flush masonry mounting - Exposed – Wall mounted					 	
Characteristics	Rigid, Plastic pipe Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories					  	
Structural material	Polyvinyl chloride (U-PVC)						
Classification EN 61386-1	<b>2 2 2 1</b>						
Compression resistance	<b>2</b>	Compression Force		320N / 5cm			
Impact Resistance	<b>2</b>	Mass	1.0 kg	Height	100mm		
Temperature Range	<b>2</b>	Lower Temperature		- 5 °C			
	<b>1</b>	Higher Temperature		+ 60 °C			
Bending Resistance	<b>1</b>	Rigid					
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance		>100MΩ	
Color	Grey- RAL 7035		Length		3m		

TYPE:	16	20	25	32	40	50
CODE:	30-210 13-016	30-210 14-020	30-210 15-025	30-210 16-032	30-210 17-040	30-210 18-050
D <sub>1</sub> External Ø / mm	16	20	25	32	40	50
D <sub>2</sub> Internal Ø / mm	14,5	18,5	23,5	30,5	38,5	48,4
Packing / m	360	225	150	75	45	45

