













COMBO SPIRAL LIGHT TYPE 320N



TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			           		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems					
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS					
Applications Installations	Indoor – Cable routing Residential and Industrial indoor installations Flush masonry mounting - Exposed					
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories					
Structural material	Polyvinyl chloride (U-PVC)					
Classification EN 61386-1	2 2 2 1					
Compression resistance	2	Compression Force	320N / 5cm			
Impact Resistance	2	Mass	1.0 kg		Height	100mm
Temperature Range	2	Lower Temperature Range	- 5 °C			
	1	Higher Temperature Range	+ 60 °C			
Bending Resistance	2	Pliable				
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ		
Color	Standard	Grey- RAL 7035	Available	Black		

TYPE:	16	20	25	32
CODE:	31-210 25-016	31-210 26-020	31-210 27-025	31-210 28-032
D₁ External Ø / mm	16	20	25	32
D₂ Internal Ø / mm	11,5	15,3	19,2	25,4
Packing – Coil / m	200	200	50	50

