
















## COURLINE DIN LIGHT TYPE 320N

### TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU					            	
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems DIN 49018-1, Dimensions reference						
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS						
Applications Installations	Indoor – Cable routing through masonry Residential and Industrial interior installations Flush masonry mounting						
Characteristics	Rigid Non Flame propagating - Self Extinguishing Externally fits as system with SPIRAL DIN LT						
Structural material	Polyvinyl chloride (U-PVC)						
Classification EN61386-1	<b>2 2 2 1</b>						
Compression resistance	<b>2</b>	Compression Force			320N / 5cm		
Impact Resistance	<b>2</b>	Mass	1.0 kg	Height	100mm		
Temperature Range	<b>2</b>	Min Temperature		- 5 °C			
	<b>1</b>	Max Temperature		+ 60 °C			
Bending Resistance	<b>1</b>	Rigid					
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance >100MΩ			
Color	Standard	White	Available	Red	Yellow	Green	Blue

<b>TYPE:</b>	<b>11</b>	<b>13,5</b>	<b>16</b>	<b>23</b>	<b>29</b>
<b>CODE:</b>	<b>13-210 35-011</b>	<b>13-210 36-013</b>	<b>13-210 37-016</b>	<b>13-210 38-023</b>	<b>13-210 34-029</b>
<b>D<sub>1</sub></b> External Ø / mm	10,5	12,6	14,9	24,4	27
<b>D<sub>2</sub></b> Internal Ø / mm	11,5	13,6	15,9	23,4	28,3
Packing – Coil / m	300	300	300	150	120

