



## SPECIAL FLEXIBLE CONDUITS


### DI FLEX CLIMA

#### TECHNICAL DATA SHEET

RoHS Compliant:	2022/95/EC Restriction of Hazardous Substances, RoHS			
Applications	Indoor	Outdoor	Residential	Industrial
	Air Condition Drainage			
Installations	Reinforced pipe			
	Exposed - Wall Mounted – On floor – On Wood - Underground			
Characteristics:	Plastic, Flexible, Sheath Spiraled Conduit			
	Profile of P-PVC, Reinforced with Spiral of U-PVC			
	Non Flame propagating - Self Extinguishing			
	Bending Radius: 10 x Ø OD			
Structural Materials:	UV Resistant			
	Profile of P-PVC, Reinforced with Spiral of U-PVC (Polyvinyl Chloride)			
	Temperature Range:			
Temperature Range:	-5 °C			
	+ 60 °C			
Color :	White (RAL 9010)			



10 x Ø OD



<b>TYPE:</b>	<b>16</b>	<b>18</b>
<b>CODE:</b>	<b>17-21001-016</b>	<b>17-21002-018</b>
<b>D<sub>1</sub> OD Ø / mm</b>	21	22
<b>D<sub>2</sub> ID Ø / mm</b>	16	18
<b>COIL / m</b>	30	30

