



## DOMO RIGID MEDIUM TYPE 750N

### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications	Indoor	Outdoor	Residential
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation		
Characteristics	Rigid, Plastic pipe Non Flame propagating - Self Extinguishing Cable management system with Support and Connection accessories UV Resistant		
Structural material	Polyvinyl chloride (U-PVC)		
Classification EN61386-1	<b>3 3 3 1</b>		
Compression resistance	<b>3</b>	Compression Force	750N / 5cm
Impact Resistance	<b>3</b>	Mass	2.0 kg
Temperature Range	<b>4</b>	Lower Temperature	- 25 °C
	<b>1</b>	Higher Temperature	+ 60 °C
Bending Resistance	<b>1</b>	Rigid	
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance >100MΩ
Color	Grey - RAL 7035	Length	3m



TYPE:	16	20	25	32	40	50
CODE:	30-210 07-016	30-210 08-020	30-210 09-025	30-210 10-032	30-210 11-040	30-210 12-050
D <sub>1</sub> OD Ø / mm	16	20	25	32	40	50
D <sub>2</sub> ID Ø / mm	13	17,5	22	29	37	46,5
Packing / m	150	150	75	75	45	45

