

## FORTE RIGID HEAVY TYPE 1250N



### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU					
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems					
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS					
Applications Installations	Indoor	Outdoor	Residential	Industrial	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation	
Characteristics	Rigid, Plastic pipe Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories UV Resistant					
Structural material	Polyvinyl chloride (U-PVC)					
Classification: EN 61386-1	<b>4 4 4 1</b>					
Compression resistance	<b>4</b>	Compression Force	1250N / 5cm			
Impact Resistance	<b>4</b>	Mass	2.0 kg	Height	300mm	
Temperature Range	<b>4</b>	Lower Temperature	- 25 °C			
	<b>1</b>	Higher Temperature	+ 60 °C			
Bending Resistance	<b>1</b>	Rigid				
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance		>100MΩ
Color	Grey - RAL 7035		Length	3m		



TYPE:	16	20	25	32	40	50
CODE:	30-210 01-016	30-210 02-020	30-210 03-025	30-210 04-032	30-210 05-040	30-210 06-050
D <sub>1</sub> ODØ / mm	16	20	25	32	40	50
D <sub>2</sub> IDØ / mm	12,5	17	21,5	28,5	36,5	46
Packing / m	150	150	75	75	45	45

