



FLUSH MOUNTING BOXES

FRAME SWITCH BOX

TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU		
Directives & Standards	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements		
Amount of Halogen Acid Gas:	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014		
Applications	Internal - Residential - Industrial Plastic box for Installation – One / Multi Gang mechanisms Lighting Switches, Plug Sockets etc Standard combination distance 71 mm		
Installations	Horizontal or vertical Joining Knockout entries for Conduits, Cables. – Max Ø20mm Flush mounting – Masonry		
Structural Material	Modified Thermoplastic Polyolefin		
Characteristics	IP Rate	3X	
	Glow Wire Test	650 °C	
	UV Resistance	LR	
	Chemicals Resistance	R	
	Dielectric strength	400V	
	Temperature Range	-15 °C	+60 °C
	Color	Black	



Switch Combinations



TYPE	FRAME
CODE	08-21022-002
A Ø / mm	75
B Ø / mm	41
C / mm	60
Packing / pcs	100

