









## FLEXIBLE CONDUITS ACCESSORIES

### COUPLINGS / RACOR > COURFLEX

#### TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU				     
Directives & Standards:	EN 61386-1:2008 & EN 61386-1:2008/A1:2019 EN 61386-23:2004 + A11:2010 Flexible Conduits System EN 61386-1:2008 & EN 61386-1:2008/A1:2019 EN 60529 Degrees of Protection - IP Rating				
RoHS Compliant	2022/95/EC Restriction of Hazardous Substances, RoHS				
Applications	In Door	Out Door	Industrial	Residencial	
Installations	Conduits Rooting Management. Conjunction and Sealing conduits to terminating devices, electrical equipment and enclosures. Wiring : Power – Lighting – Automation – Data – Telecoms				
Χαρακτηριστικά:	Attach and secure the end of an conduit to the equipment screwed with a hexagonal locknut ISO metric screw thread				
Υλικό Κατασκευής:	Thermoplastic Polymer				
IP Rating	Protection Solid	<b>X5</b>	Protection Water	<b>X4</b>	
Temperature Range	- 15 °C + 60 °C				
Color	Grey (RAL 7035)				

TYPE:	12	16	20	25	32
CODE:	<b>33-200 08-012</b>	<b>33-200 09-016</b>	<b>33-200 10-020</b>	<b>33-200 11-025</b>	<b>33-200 12-032</b>
A Ø / mm - Install	16	20	25	32	40
B Ø / mm - Min ID	10.3	14.2	17.6	22.5	29.8
C Ø / mm - Pipe Type	12	16	20	25	32
M Thread / mm	M16x1.5	M20x1.5	M25x1.5	M32x1.5	M40x1.5

