














## CONDUITS CONNECTION & SUPPORT ACCESSORIES

### SIBI COUPLINGS

#### TECHNICAL DATA SHEET

|                         |  |   |
|-------------------------|--|---|
| Reference:              | LVD 2014/35/EU   |    |
| Directives & Standards: | EN 61386-1:2008 Cable Management General Requirements<br>EN 61386-22:2004 + A11:2010 Pliable Conduit Systems<br>DIN 49018-1 (Pipes Diameter) |    |
| RoHS Compliant:         | 2022/95/EC Restriction of Hazardous Substances, RoHS   |    |
| Applications            | Indoor - Outdoor<br>Residential and Industrial Installations<br>Cable Routing  |    |
| Installations           | Underground Installations<br>Infloor Installations<br>Encased in Concrete  | <br>   |
| Characteristics:        | Ingress Protection Rating: IP54<br>Self Extinguishing - Flame Retardant<br>UV Protection   | <br><br> |
| Structural Material:    | Polyvinyl Chloride (P-PVC)   |    |
| Temperature Range:      | - 15 °C<br>+ 60 °C   |    |
| Color / available:      | Grey (RAL 7035)  |   |

| TYPE:            | 11               | 13,5             | 16               | 23               |
|------------------|------------------|------------------|------------------|------------------|
| CODE:            | 21-210<br>01-011 | 21-210<br>02-013 | 21-210<br>03-016 | 21-210<br>04-023 |
| A / mm           | 90               | 90               | 90               | 90               |
| Outside Ø B / mm | 20,4             | 24               | 27               | 34,5             |
| D Ø Pipe / mm    | 17               | 20               | 23               | 30,5             |
| PACKAGING (pcs): | 50               | 50               | 50               | 25               |

