














CONDUITS CONNECTION & SUPPORT ACCESSORIES

TUBODIN COUPLINGS

TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU	
Directives & Standards:	EN 61386-1:2008 Cable Management General Requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems DIN 49018-1 (Pipes Diameter)	
RoHS Compliant:	2022/95/EC Restriction of Hazardous Substances, RoHS	
Applications	Indoor - Outdoor Residential and Industrial Installations Cable Routing	
Installations	Underground Installations Infloor Installations Encased in Concrete	 
Characteristics:	Ingress Protection Rating: IP54 Self Extinguishing - Flame Retardant UV Protection	  
Structural Material:	Polyvinyl Chloride (U-PVC)	
Temperature Range:	- 15 °C + 60 °C	
Color / available:	Blue (RAL 5015)	

TYPE:	11	13,5	16	23
CODE:	21-210 10-011	21-210 11-013	21-210 12-016	21-210 13-023
A / mm	90	90	90	90
B OD Ø / mm	19,4	23,5	26	33,5
D Ø Pipe / mm	16	19,5	22	29,5
PACKAGING (pcs):	100	100	100	50

