



# WATERTIGHT JUNCTION BOXES

## PRESS-ON LID & KNOCK OUTS - IP65

## 80x80

### TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU					
Standards Amends	EN 60670-1:2005+A1:2013 Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements EN 60529 Degrees of Protection , Enclosures, IP Rate					
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS					
Applications	Indoor – Outdoor - Residential – Industrial Plastic box with Press-On Lid Wiring, Junction or Extension – General Propose					
Installations	Exposed – Wall mounted					
	Wiring, Power, Lighting, Automation, Telecom, CCTV,					
Material	Polyvinyl Chloride > U-PVC					
Characteristics	IP Rate	Solid	6	Water	5	
	Glow Wire Test	850 °C				
	Resistance - UV	R				
	Resistance - Chemicals	R				
	Resistance - Fire	FR-SE				
	Dielectric Strength	+400V				
	Temperature range	-15 °C		+60 °C		
	Color	Grey RAL7035				



<b>TYPE</b>	<b>80x80</b>
<b>CODE</b>	32-21040-808
<b>A_mm</b>	80
<b>B_mm</b>	80
<b>C / mm</b>	40
<b>D Max ODØ_mm</b>	25
<b>PACKING / pcs</b>	60

