



PLIABLE CONDUITS CORRUGATED

01

SPIRAL DIN - Light Type 320N



PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinil Chloride (U-PVC)
- Compression resistant : Light
- No flame propagation, Self Extinguishing

APPLICATIONS - INSTALLATIONS

- Indoor - Residential - Industrial
- Flush mounted
- Cable Protection and Routing through masonry
- Rigid pipe **COURLINE DIN E/T** fits Internally as system

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
03-21035-011	11	15,8	12,4	50	200
03-21036-013	13,5	19	14,7	50	200
03-21037-016	16	21,5	17	50	200
03-21038-023	23	29	24,4	25	100
03-21034-029	29	34,8	29,3	25	50



EN.61386-22/2004
EN.61386-1/2008
DIN 49018-1



COMBO SPIRAL - Light Type 320N



PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinil Chloride (U-PVC)
- Compression resistant : Light
- No flame propagation, Self Extinguishing

APPLICATIONS - INSTALLATIONS

- Indoor - Residential - Industrial
- Flush mounted
- Cable Protection and Routing through masonry
- Cable Management System with support and connection accessories

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
31-21025-016	16	16	11,5	50	200
31-21026-020	20	20	15,3	50	200
31-21027-025	25	25	19,2	50	50
31-21028-032	32	32	25,4	50	50



EN.61386-1/2008
EN.61386-22/2004



COMBO SPIRAL - Light Type 320N + Wire



PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinil Chloride (U-PVC)
- Compression resistant : Medium
- No flame propagation, Self Extinguishing

APPLICATIONS - INSTALLATIONS

- Indoor - Residential - Industrial
- Flush mounted
- Cable Protection and Routing through masonry
- Cable Management System with support and connection accessories
- Cable Puller inside (Galvanized Wire Ø0,8mm - TensileF_750N)

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
31-21037-016	16	16	11,5	50	200
31-21038-020	20	20	15,3	50	200
31-21039-025	25	25	19,2	50	50
31-21040-032	32	32	25,4	50	50



EN.61386-1/2008
EN.61386-22/2004



DOMO SPIRAL - Medium Type 750N



PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinyl Chloride (U-PVC)
- Compression resistant : Medium
- No flame propagation, Self Extinguishing
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Industrial
- Exposed, Wall Mounted - In floor - In concrete - On Wood
- Wiring Protection, Routing > Power - Automation - Lighting
- Cable Management System with Support and Connection Accessories

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
31-21001-016	16	16	11	50	50
31-21002-020	20	20	15	50	50
31-21003-025	25	25	19	50	50
31-21004-032	32	32	25	50	50
31-21005-040	40	40	31,5	25	25
31-21006-050	50	50	40	25	25



DOMO SPIRAL - Medium Type 750N + Wire

PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinyl Chloride (U-PVC)
- Compression resistant : Medium
- No flame propagation, Self Extinguishing
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Industrial
- Exposed, Wall Mounted - In floor - In concrete - On Wood
- Wiring Protection, Routing > Power - Automation - Lighting
- Cable Management System with Support and Connection Accessories
- Cable Puller inside (Galvanized Wire Ø0,8mm - TensileF_750N)



CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
31-21031-016	16	16	11	50	50
31-21032-020	20	20	15	50	50
31-21033-025	25	25	19	50	50
31-21034-032	32	32	25	50	50



FORTE SPIRAL - Heavy Type 1250N



PRODUCT DESCRIPTION

- Corrugated, Pliable - Spiral
- Material : Polyvinyl Chloride (U-PVC)
- Compression resistant : Heavy
- No flame propagation, Self Extinguishing
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Industrial
- Exposed, Wall Mounted - In floor - In concrete - On Wood
- Wiring Protection, Routing > Power - Automation - Lighting
- Cable Management System with Support and Connection Accessories

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
31-21007-016	16	16	10,8	25	25
31-21008-020	20	20	14,1	25	25
31-21009-025	25	25	18,3	25	25
31-21010-032	32	32	24,3	25	25
31-21011-040	40	40	31	25	25
31-21012-050	50	50	39,5	25	25

