



02

**RIGID CONDUITS
& ACCESSORIES**

COURLINE DIN Light Type 320N

PRODUCT DESCRIPTION

- Rigid Conduit
 - Material : Polyvinyl Chloride (U-PVC)
 - No flame propagation, Self Extinguishing
- APPLICATIONS - INSTALLATIONS**
- Indoor - Residential - Industrial
 - Flush mounted
 - Cable Protection and Routing through masonry
 - SPIRAL DIN L/T fits Externally as system

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
13-21035-011	11	11,5	10,5	3	300
13-21036-013	13,5	13,6	12,6	3	300
13-21037-016	16	15,9	14,9	3	300
13-21038-023	23	23,4	22,4	3	150
13-21034-029	29	28,3	27	3	120


 EN.61386-21/2004
 EN.61386-1/2008
 DIN 49018-1

COMBO RIGID Light Type 320N

PRODUCT DESCRIPTION

- Rigid Conduit
 - Material : Polyvinyl Chloride (U-PVC)
 - No flame propagation, Self Extinguishing
- APPLICATIONS - INSTALLATIONS**
- Indoor - Residential - Industrial
 - Flush mounted
 - Cable Protection and Routing through masonry
 - Cable Management System with Support and Connection Accessories

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
30-21013-016	16	16	14,5	3	360
30-21014-020	20	20	18,5	3	225
30-21015-025	25	25	23,5	3	150
30-21016-032	32	32	30,5	3	75
30-21017-040	40	40	38,5	3	45
30-21018-050	50	50	48,4	3	45


 EN.61386-1/2008
 EN.61386-21/2004

DOMO RIGID Medium Type 750N

PRODUCT DESCRIPTION

- Rigid Conduit
 - Material : Polyvinyl Chloride (U-PVC)
 - Compression resistant : Medium
 - No flame propagation, Self Extinguishing
 - UV Resistant
- APPLICATIONS - INSTALLATIONS**
- Indoor - Outdoor, Residential - Industrial
 - Exposed, Wall Mounted - In floor - In concrete - On Wood
 - Wiring Protection, Routing > Power - Automation - Lighting
 - Cable Management System with Support and Connection Accessories
 - Recommended: Supports installation per 50cm

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
30-21007-016	16	16	13	3	150
30-21008-020	20	20	17,5	3	150
30-21009-025	25	25	22	3	75
30-21010-032	32	32	29	3	75
30-21011-040	40	40	37	3	45
30-21012-050	50	50	46,5	3	45


 EN.61386-1/2008
 EN.61386-21/2004

FORTE RIGID Heavy Type 1250N

PRODUCT DESCRIPTION

- Rigid Conduit
 - Material : Polyvinyl Chloride (U-PVC)
 - Compression resistant : Heavy
 - No flame propagation, Self Extinguishing
 - UV Resistant
- APPLICATIONS - INSTALLATIONS**
- Indoor - Outdoor - Residential - Industrial
 - Exposed, Wall Mounted - In floor - In concrete - On Wood
 - Wiring Protection, Routing > Power - Automation - Lighting
 - Cable Management System with Support and Connection Accessories
 - Recommended: Supports installation per 50cm

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		D1/mm	D2/mm		
30-21001-016	16	16	12,5	3	150
30-21002-020	20	20	17	3	150
30-21003-025	25	25	21,5	3	75
30-21004-032	32	32	28,5	3	75
30-21005-040	40	40	36,5	3	45
30-21006-050	50	50	46	3	45


 EN.61386-1/2008
 EN.61386-21/2004


COUPLING



PRODUCT DESCRIPTION - APPLICATIONS

- Join two runs of Conduits
- Material : Polyvinyl Chloride (U-PVC)
- No flame propagation, Self Extinguishing
- Ingress Protection : IP54
- Fits with SPIRAL and RIGID

CODE	TYPE	OD CONDUIT	PACKING Pcs
38-21001-016	16	Ø 16mm	50
38-21002-020	20	Ø 20mm	50
38-21003-025	25	Ø 25mm	50
38-21004-032	32	Ø 32mm	10
38-21005-040	40	Ø 40mm	10
38-21006-050	50	Ø 50mm	10

BEND 90°



PRODUCT DESCRIPTION - APPLICATIONS

- Join like with like and introduce a curve to the length of conduit
- Material : Polyvinyl Chloride (U-PVC)
- No flame propagation, Self Extinguishing
- Ingress Protection : IP54
- Fits with SPIRAL and RIGID conduits

39-21007-016	16	Ø 16mm	50
39-21008-020	20	Ø 20mm	50
39-21009-025	25	Ø 25mm	10
39-20010-032	32	Ø 32mm	5
39-20011-040	40	Ø 40mm	5
39-20012-050	50	Ø 50mm	5

INSPECTIONABLE BEND 90°



PRODUCT DESCRIPTION - APPLICATIONS

- Join like with like and introduce a bend to the length of conduit
- Divided in 2 pieces for Cable Inspection - Management
- Material : Polyvinyl Chloride (U-PVC)
- No flame propagation, Self Extinguishing
- Ingress Protection : IP54
- Fits with SPIRAL and RIGID conduits

36-20001-016	16	Ø 16mm	10
36-20002-020	20	Ø 20mm	10
36-20003-025	25	Ø 25mm	10
36-20004-032	32	Ø 32mm	5

INSPECTIONABLE "T" JOIN



PRODUCT DESCRIPTION - APPLICATIONS

- Join like with like and introduce a T Junction of a conduit run
- Divided in 2 pieces for Cable Inspection - Junction
- Material : Polyvinyl Chloride (U-PVC)
- No flame propagation, Self Extinguishing
- Ingress Protection : IP54
- Fits with SPIRAL and RIGID conduits

37-20001-016	16	Ø 16mm	10
37-20002-020	20	Ø 20mm	10
37-20003-025	25	Ø 25mm	10
37-20004-032	32	Ø 32mm	5

SNAP CLIPS



PRODUCT DESCRIPTION - APPLICATIONS

- SNAP Clip, secures the Conduit run to wall or joist
- Installations: Exposed Wall Mounted
- Ability to connect and assemble on a rail
- No flame propagation, Flame Retardant
- Halogen Free
- Recommended installation per 50cm
- Fits with SPIRAL and RIGID conduits

34-21001-016	16	Ø 16mm	100
34-21002-020	20	Ø 20mm	100
34-21003-025	25	Ø 25mm	100
34-21004-032	32	Ø 32mm	100
34-21005-040	40	Ø 40mm	50
34-21006-050	50	Ø 50mm	50

OMEGA CLIPS



PRODUCT DESCRIPTION - APPLICATIONS

- OMEGA Clip, secures the conduit run to Wall or Ceiling
- Installations: Exposed Wall Mounted
- Ability to connect and assemble on a rail
- No flame propagation, Flame Retardant
- Halogen Free
- Recommended installation per 50cm
- Fits with SPIRAL and RIGID conduits

41-20001-016	16	Ø 16mm	100
41-20002-020	20	Ø 20mm	100
41-20003-025	25	Ø 25mm	50
41-20004-032	32	Ø 32mm	50

RACOR JOIN Pipe - Box



PRODUCT DESCRIPTION - APPLICATIONS

- Connect Conduit run to an Watertight Box
- Material : Polyvinyl Chloride (U-PVC)
- No flame propagation, Self Extinguishing
- Ingress Protection : IP54
- Fits with SPIRAL and RIGID conduits

33-21001-016	16>D23	Ø 16mm	10
33-21007-016	16>D29	Ø 16mm	10
33-21002-020	20>D23	Ø 20mm	10
33-21008-020	20>D29	Ø 20mm	10
33-21009-025	25>D29	Ø 25mm	10



EN.61386-1/2008

