











CABLE TRUNKING

PLASTIC CABLE TRUNKING With INSTALLATION ADHESIVE TAPE

TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU		
Standards Amends	EN 50085-1:2005+A1:2013 - General requirements Cable Trunking /Ducting systems for electrical installations EN 50085-2-1:2006/A1:2011 Cable Trunking / Ducting systems intended for mounting on walls and ceilings		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications	Indoor – Outdoor - Residential – Industrial Plastic rigid Trunking with Removable cover and Installation Adhesive Tape		
Installations	Exposed – Wall mounted - OnFloor		
	Wiring, Power, Lighting, Telecom, CCTV, AUDIO, SAT, TV, FIBER <div style="display: flex; justify-content: space-around; align-items: center; margin-top: 5px;">         </div>		
Material	Polyvinyl Chloride > U-PVC		
Characteristics	Glow Wire Test		800 °C
	Resistance - UV		R
	Resistance - Chemicals		R
	Resistance - Fire		FR-SE
	Temperature Range		-15 °C +60 °C
	Color	White – RAL9010	Length



TYPE:	12x12	16x16	20x10	25x16	25x25	40x40
CODE:	24-200 30-121	24-200 31-161	24-200 32-201	24-200 33-251	24-200 34-252	24-200 35-404
DIAMENTIONS A x B / mm:	12x12	16x16	20x10	25x16	25x25	40x40
PACKING / pcs:	180	224	132	140	90	72

