



## DOMO RIGID + SLEEVE MEDIUM TYPE 750N

### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications	Indoor	Outdoor	Residential Industrial
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation		
Characteristics	Rigid, Plastic conduit 3m length sleeved one edge. This sleeved out end is designed to fit directly onto the next length of pipe attached . Cable management system with Support and connection accessories Non Flame propagating - Self Extinguishing. UV Resistant		
Structural material	Polyvinyl chloride (U-PVC)		
Classification EN61386-1	<b>3 3 3 1</b>		
Compression resistance	<b>3</b>	Compression Force	750N / 5cm
Impact Resistance	<b>3</b>	Mass 2.0 kg	Height 100mm
Temperature Range	<b>4</b>	Lower Temperature	- 25 °C
	<b>1</b>	Higher Temperature	+ 60 °C
Bending Resistance	<b>1</b>	Rigid	
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance >100MΩ
Color	Grey - RAL 7035	Length	3m
<b>TYPE:</b>	<b>16</b>	<b>20</b>	<b>25</b>
<b>CODE:</b>	<b>30-21100-016</b>	<b>30-21101-020</b>	<b>30-21102-025</b>
<b>D<sub>1</sub> OD Ø / mm</b>	16	20	25
<b>D<sub>2</sub> ID Ø / mm</b>	13	17,5	22
Packing / m	150	150	75

