

DRY WALL ELECTRICAL INSTALLATION MATERIALS



SINGLE – 1GANG SWITCH BOX


TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU		
Directives & Standards	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements		
Halogen Acid Gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014		
Applications	Internal - Residential - Industrial Plastic box for Installation - various one-Gang elements Lighting Switches, Plug Sockets etc		
Installations	Knockout entries for Conduits, Cables Flush mount – Dry / Hollow walls - Gypsum plasterboard		
Structural Material	Modified Thermoplastic Polyolefin		
Characteristics	IP Rate	3X	
	Glow Wire Test	650 °C	
	UV Resistance	LR	
	Chemicals Resistance	R	
	Dielectric strength	400V	
	Temperature Range	-15 °C	+60 °C
	Color	Yellow (RAL 1021)	



Switch Combinations



TYPE	SINGLE	INSTALLATION
CODE	08-21048-001	
D / mm	67	
C / mm	50	
Packing/ pcs	100	

