



DOMO RIGID + SLEEVE MEDIUM TYPE 750N

TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications	Indoor	Outdoor	Residential Industrial
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation		
Characteristics	Rigid, Plastic conduit 3m length sleeved one edge. This sleeved out end is designed to fit directly onto the next length of pipe attached . Cable management system with Support and connection accessories Non Flame propagating - Self Extinguishing. UV Resistant		
Structural material	Polyvinyl chloride (U-PVC)		
Classification EN61386-1	3 3 4 1		
Compression resistance	3	Compression Force	750N / 5cm
Impact Resistance	3	Mass	2.0 kg
Temperature Range	4	Lower Temperature	- 25 °C
	1	Higher Temperature	+ 60 °C
Bending Resistance	1	Rigid	
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance >100MΩ
Color	Grey - RAL 7035	Length	3m
TYPE:	16	20	25
CODE:	30-21100-016	30-21101-020	30-21102-025
D₁ OD Ø / mm	16	20	25
D₂ ID Ø / mm	13	17,5	22
Packing / m	150	150	75

