

## DOMO RIGID MEDIUM TYPE 750N



### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU					
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems					
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS					
Applications	Indoor	Outdoor	Residential	Industrial		
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation					
Characteristics	Rigid, Plastic pipe Non Flame propagating - Self Extinguishing Cable management system with Support and Connection accessories UV Resistant					
Structural material	Polyvinyl chloride (U-PVC)					
Classification EN61386-1	<b>3 3 4 1</b>					
Compression resistance	<b>3</b>	Compression Force	750N / 5cm			
Impact Resistance	<b>3</b>	Mass	2.0 kg	Height	100mm	
Temperature Range	<b>4</b>	Lower Temperature	- 25 °C			
	<b>1</b>	Higher Temperature	+ 60 °C			
Bending Resistance	<b>1</b>	Rigid				
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance		>100MΩ
Color	Grey - RAL 7035		Length	3m		



<b>TYPE:</b>	<b>16</b>	<b>20</b>	<b>25</b>	<b>32</b>	<b>40</b>	<b>50</b>
CODE:	30-210 07-016	30-210 08-020	30-210 09-025	30-210 10-032	30-210 11-040	30-210 12-050
D <sub>1</sub> OD Ø / mm	16	20	25	32	40	50
D <sub>2</sub> ID Ø / mm	13	17,5	22	29	37	46,5
Packing / m	150	150	75	75	45	45

