




EL FLEX MULTILAYER PLIABLE CONDUITS

TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU		
Standards Amends	EN 61386-1:2008 Cable Management, General requirements EN 61386-24:2010 Conduit systems buried underground		
Halogen acid gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014		
Description	Plastic Multilayer Conduit, Pliable / Corrugated		
Applications	Underground - Outdoor		
Installations	Cable Protection, Routing Management - Buried underground		
	Infrastructures, Road Lighting, Power, Telecom, R.E.S		
Structural material	Modified Thermoplastic Polyolefin		
Characteristics	Resistance - Compression	> 750N	
	Resistance - Impact	N	20 Joule
	Resistance - UV	R	
	Resistance - Chemicals	R	
	Bending Rdius - Min	10 x Ø OD	
	IP Rate	IP 65	
	Temperature Range	-25 °C	+60 °C
	Color	Black	



IP65



TYPE:	32	40	50	60
CODE:	05-21008-032	05-21009-040	05-21010-050	05-21011-060
D ₁ OD Ø / mm	32	40	50	60
D ₂ ID Ø / mm	25	31	39	50
Packing / m	50	25	25	25

