



COMBO SPIRAL ECO + Wire LIGHT TYPE 320N

TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications Installations	Indoor – Cable routing Residential and Industrial indoor installations Flush masonry mounting		
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories With Cable puller - (Galvanized Wire - Ø0,8mm – Tensile F750N)		
Structural material	Polyvinyl chloride (U-PVC)		
Classification EN 61386-1	2 2 2 1		
Compression resistance	2	Compression Force	320N / 5cm
Impact Resistance	2	Mass	1.0 kg
Temperature Range	2	Lower Temperature Range	- 5 °C
	1	Higher Temperature Range	+ 60 °C
Bending Resistance	2	Pliable	
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance >100MΩ
Color	Black		



TYPE:	16	20	25	32
CODE:	31-210 60-016	31-210 61-020	31-210 62-025	31-210 63-032
D ₁ External Ø / mm	16	20	25	32
D ₂ Internal Ø / mm	11,5	15,3	19,2	25,4
Packing – Coil / m	200	200	50	50

