

DOMO SPIRAL ECO+WIRE MEDIUM TYPE 750N

TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems			
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS			
Applications	Indoor	Outdoor	Residential	Industrial
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation			
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing With Cable puller - (Galvanized Wire - Ø0,8mm – Tensile F750N) Cable management system with Support and connection accessories UV Resistant			
Structural material	Polyvinyl chloride (U-PVC)			
Classification EN 61386-1	3 3 4 1			
Compression resistance	3	Compression Force	750N / 5cm	
Impact Resistance	3	Mass	2.0 kg	Height 100mm
Temperature Range	4	Lower Temperature range	- 25 °C	
	1	Higher Temperature range	+ 60 °C	
Bending Resistance	2	Pliable		
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ
Color	Black			



TYPE:	16	20	25	32
CODE:	31-211 06-016	31-211 07-020	31-211 08-025	31-211 09-032
D₁ External Ø / mm	16	20	25	32
D₂ Internal Ø / mm	11	15	19	25
Packing – Coil / m	100	100	75	50

