















COMBO SPIRAL + Wire LIGHT TYPE 320N

TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			           	
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems				
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS				
Applications Installations	Indoor – Cable routing Residential and Industrial indoor installations Flush masonry mounting				
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories With Cable puller - (Galvanized Wire - Ø0,8mm – Tensile F750N)				
Structural material	Polyvinyl chloride (U-PVC)				
Classification EN 61386-1	2 2 2 1				
Compression resistance	2	Compression Force	320N / 5cm		
Impact Resistance	2	Mass	1.0 kg		Height
Temperature Range	2	Lower Temperature Range	- 5 °C		
	1	Higher Temperature Range	+ 60 °C		
Bending Resistance	2	Pliable			
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ	
Color	Standard	Grey- RAL 7035			

TYPE:	16	20	25	32
CODE:	31-210 37-016	31-210 38-020	31-210 39-025	31-210 40-032
D ₁ External Ø / mm	16	20	25	32
D ₂ Internal Ø / mm	11,5	15,3	19,2	25,4
Packing – Coil / m	200	200	50	50

