










PIPE TERMINAL VERTICAL




PIPE TERMINAL BEND 30°



TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU	
Directives & Standards:	EN 61386-1:2008 Cable Management General Requirements DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014	
RoHS Compliant:	2022/95/EC Restriction of Hazardous Substances, RoHS	
Applications	Indoor - Outdoor Residential and Industrial Installations	
Installations	Wiring Ends - Standby. Encased in concrete slab	
Characteristics:	Pipes Plug In Adapters - Nailed to the formwork. Terminal adaptor : Vertical Terminal adaptor : Bend 30° Snap-Fit Conduits \varnothing 20mm up to \varnothing 25mm	 
Structural Material:	Modified Thermoplastic Polyolefin	
Temperature Range:	- 15 °C + 60 °C	
Color / available:	Red	

TYPE :	BETON ADAPTER VERTICAL
CODE :	29-20001-001
A / mm	55
B ίκη \varnothing / mm	50
Packaging (pcs):	20



TYPE :	BETON ADAPTER BEND 30°
CODE :	29-20002-002
A / mm	55
B ίκη \varnothing / mm	50
Packaging (pcs):	20

