


**MODUL  
3 GANG**

**MODUL  
4 GANG**

**MODUL  
6 GANG**

## TECHNICAL DATA SHEET

Reference	LVD 2014/35/EU		
Directives & Standards	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements		
Halogen Acid Gas Vol	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014		
Applications	Εσωτερική Χρήση > Οικιακές, Επαγγελματικές Ηλεκ. Εγκαταστάσεις		
	Internal > Residential - Professional - Prefab		
	Ξηράς Δόμησης – Γυψοσανίδες, Τσιμεντοσανίδες		
Installations	Flush mount – Dry / Hollow walls - Gypsum plasterboard		
	Πλαστικό κουτί εγκατάστασης Διακοπτικού Υλικού MODUL		
	Plastic box for Installation – Multi Gang mechanisms MODUL		
Structural Material	Αποσπώμενες εισόδους – Up to Ø25mm		
	Knockout entries for Conduits, Cables – Up to Ø25mm		
Characteristics	Structural Material	Modified Thermoplastic Polyolefin	
	IP Rate	3X	
	Glow Wire Test	850 °C	
	UV Resistance	LR	
	Chemicals Resistance	R	
	Dielectric strength	400V	
	Temperature Range	-15 °C	+60 °C
	Color	Yellow	


**Mechanisms**


ΤΥΠΟΣ	MODUL.3	MODUL.4	MODUL.6
ΚΩΔΙΚΟΣ	08-21046-003	08-20015-004	08-20016-006
A / mm	65	65	65
B / mm	110	135	188
C / mm	50	50	50
Συσκευασία / pcs	50	40	30

**INSTALLATION  
HOLES**
