



04

**FLEXIBLE
SPIRALED CONDUITS**

FLEXIBLE CONDUITS & ACCESSORIES



Courflex®



PRODUCT DESCRIPTION

- Flexible conduit, Spiraled Sheath
- Material : Profile of P-PVC reinforced with spiral U-PVC
- Compression resistant : Light 320N
- No flame propagation, Self Extinguishing
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Industrial
- Exposed, Wall Mounted - On floor - On Wood
- Cable Protection and Routing
- Wiring > Power, Automation, Lighting, Telecoms
- Conjunction and Sealing with Connectors to terminating devices - Enclosures

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
16-21060-010	10	13,3	10	30	30
16-21012-012	12	16	12	30	30
16-21013-014	14	16,4	14	30	30
16-21014-016	16	20	16	30	30
16-21015-018	18	21,2	18	30	30
16-21016-020	20	22,5	20	30	30
16-21017-022	22	25,3	22	30	30
16-21018-025	25	28,1	25	30	30
16-21019-030	30	36	30	30	30
16-21070-032	32	37	32	30	30
16-21021-038	38	44,5	38	30	30
16-21071-040	40	47	40	30	30
16-21022-050	50	55,5	50	30	30
16-21023-062	62	69	62	30	30



Courflex® - Clima



PRODUCT DESCRIPTION

- Flexible conduit, Spiraled Sheath
- Material : Profile of P-PVC reinforced with spiral U-PVC
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Professional
- Exposed, Wall Mounted - On floor - On Wood
- Drainage : Air Condition - Refrigeration Units
- Conjunction with Connectors

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
16-21048-012	12	16	12	30	30
16-21049-014	14	16,4	14	30	30
16-21050-016	16	20	16	30	30
16-21051-018	18	21,2	18	30	30
16-21052-020	20	22,5	20	30	30
16-21053-022	22	25,3	22	30	30
16-21054-025	25	28,1	25	30	30



Di Flex Clima




PRODUCT DESCRIPTION

- Reinforced Flexible conduit, Spiraled Sheath
- Material : Profile of P-PVC reinforced with spiral U-PVC
- Compression resistant : Light >320N
- UV Resistant

APPLICATIONS - INSTALLATIONS

- Indoor - Outdoor - Residential - Industrial
- Exposed, Wall Mounted - On floor - On Wood
- Power Supply - Drainage : Air Condition - Refrigeration Units
- Electrical Installations

CODE	TYPE	DIAMETER		LENGTH m	PACKING m
		OD/mm	ID/mm		
17-21001-016	16	21	16	30	30
17-21002-018	18	22	18	30	30



GLAND JOIN Courflex > Box



DESCRIPTION - APPLICATIONS

- Screwed-Fit Join Conduit run to : Terminating Devices, Enclosures
- Locknut, ISO Metric screw thread
- Ingress Protection : IP54

CODE	TYPE	DIMENSIONS		THREAD Metric	PACKING/pc	
		ØA/mm	ØC/mm		Bag	Box
33-20008-012	12	D23	12	M16x1.5	100	1200
33-20009-016	16	D23	16	M20x1.5	100	800
33-20010-020	20	D29	20	M25x1.5	100	500
33-20011-025	25	D37	25	M32x1.5	50	300
33-20012-032	32	D37	32	M40x1.5	40	160

