













HALOGEN FREE CONDUITS

SPIRAL HF LIGHT TYPE 320N

TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU					
Directives & Standards:	EN 61386-1:2008 Cable Management, General Requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems					
Halogen Acid Gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014					
Applications	Indoor Residential and Industrial Installations			 		
Installations	Cable Routing Flush Installations					
Characteristics	Pliable, Corrugated – Spiral Cable Management Connection and Mounting Accessories available			 		
Material	Modified Thermoplastic Polyolefin					
Classification: EN 61386-1	2 3 3 2					
Compression Resistance	2	Compression Force	320N / 5cm			
Impact Resistance	3	Mass	2.0 kg	Height	100mm	
Temperature Range:	3	Lower Temperature	- 15 °C			
	2	Higher Temperature	+ 90 °C			
Electrical Properties:	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ		
Color	Standard	Gray RAL 7035	Other colors available on request			

TYPE:	16	20	25	32	40	50
CODE:	07-210 07-016	07-210 08-020	07-210 09-025	07-210 10-032	07-210 11-040	07-210 12-050
D ₁ OD Ø / mm	16	20	25	32	40	50
D ₂ ID Ø / mm	10,7	14,5	19	24,3	31,2	39,6
Packing – Coil / m	100	100	50	50	25	25

