



DOMO RIGID + SLEEVE MEDIUM TYPE 750N

TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems			
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS			
Applications Installations	Indoor	Outdoor	Residential	Industrial
Characteristics	Rigid, Plastic conduit 3m length sleeved one edge. This sleeved out end is designed to fit directly onto the next length of pipe attached . Cable management system with Support and connection accessories Non Flame propagating - Self Extinguishing. UV Resistant			
Structural material	Polyvinyl chloride (U-PVC)			
Classification EN61386-1	3 3 4 1			
Compression resistance	3	Compression Force	750N / 5cm	
Impact Resistance	3	Mass	2.0 kg	Height 100mm
Temperature Range	4	Lower Temperature	- 25 °C	
	1	Higher Temperature	+ 60 °C	
Bending Resistance	1	Rigid		
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance >100MΩ
Color	Grey - RAL 7035		Length	3m

TYPE:	16	20	25	32
CODE:	30-21100-016	30-21101-020	30-21102-025	30-21103-032
D ₁ OD Ø / mm	16	20	25	32
D ₂ ID Ø / mm	13	17,5	22	29
Packing / m	150	150	75	75

