




DUPLEX SPIRAL HFFR DRYWALL COUPLING - ΜΟΥΦΕΣ

TECHNICAL DATA SHEET

Reference :	LVD 2014/35/EU			
Standards :	EN 61386-1:2008 Cable Management, General requirements EN 60529 IP Rating			
Smoke Density :	DIN EN 61034-2 (VDE0482-1034-2)2014-11:EN 61034-2:2005+A1:2013			
Acidity :	DIN EN 60754-2 (VDE 0482-754-2) : 2015-08 EN 60754-2:2014			
Halogen acid gas Amount :	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014			
Applications Installations	Εσωτερική Χρήση > Οικιακές - Επαγγελματικές Ηλεκτρ. Εγκ/σεις <i>Indoor – Prefab > Residential - Industrial - Commercial</i>			
Characteristics :	Σύνδεση Σωληνώσεων DUPLEX SPIRAL DryWall			
	<i>Joins two runs of DUPLEX SPIRAL DryWall</i>			
	Δεν διαδίδουν Φλόγα, Αυτοσβηνόμενα - (FR-SE)			
	<i>Non Flame propagating - Self Extinguishing</i>			
	Σε περίπτωση πυρκαγιάς δεν εκπέμπουν Αλογόνα οξέα. <i>In case of fire they don't release Halogen acids</i> (Chlorine, Fluorine, Bromine, Iodine, Astatine)			
Structural material :	Modified Thermoplastic Polyolefin			
IP Rating :	SOLID	X5	LIQUID	X4
Temperature Range :	- 25 °C			
	+ 105 °C			
Color :	Yellow			



DUPLEX DRYWALL COUPLINGS

TYPE :	16	20	25	
CODE :	38-21010-016	38-21011-020	38-21012-025	38-21032-032
A / mm	60,3	69,5	78,9	88,5
Ø B / mm	21,2	24,4	29,9	36,3
D Ø Pipe / mm	16	20	25	32
Packing / pcs	50	50	50	10

