



COMBO SPIRAL - ECO LIGHT TYPE 320N



TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			
Standards	EN 61386-1:2008 Cable Management, General requirements			
	EN 61386-22:2004 + A11:2010 Pliable Conduit Systems			
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS			
ECO Solution	With a low environmental footprint contributing to the reduction of CO ₂ and the consumption of fossil fuels.			
Applications	Indoor use			
	Residential, Professional Electrical Installations			
Installations	Cables protection, Management, Routing			
	Flush masonry mounting			
Characteristics	Pliable, Corrugated – Spiral			
	Non Flame propagating - Self Extinguishing			
	Contribute to reducing the environmental footprint of constructions			
Structural material	Polyvinyl chloride (U-PVC)			
Classification EN 61386-1	2 2 2 1			
Compression resistance	2	Compression Force	320N / 5cm	
Impact Resistance	2	Mass	1.0 kg	
Temperature Range	2	Lower Temperature Range	- 5 °C	
	1	Higher Temperature Range	+ 60 °C	
Bending Resistance	2	Pliable		
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ
	Color	Black		



TYPE:	16	20	25	32
CODE:	31-210 50-016	31-210 51-020	31-210 52-025	31-210 53-032
D ₁ External Ø / mm	16	20	25	32
D ₂ Internal Ø / mm	11,5	15,3	19,2	25,4
Packing – Coil / m	200	200	50	50

