


















DOMO RIGID HFFR - ECO MEDIUM TYPE 750N



TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-21:2004 + A11:2010 Rigid Conduit Systems			
Smoke Density	EN 61034-2 : 2005 + A2:2020 EN 61034-2:2005+A1:2013			
Acidity	EN 60754-2 : 2012 + A1:2022 EN 60754-2:2014			
Halogen & Acid Gas	EN 60754-1 : 2014 + A1:2020 EN 60754-1:2014			
ECO Solution	With a low environmental footprint contributing to the reduction of CO2 and the consumption of fossil fuels.			
Applications	Outdoor, Indoor Residential – Industrial Electrical Installations			
	Contribute to reducing the environmental footprint of constructions			
Installations	Exposed - Wall mounted - Flush masonry			
	Cables protection, Management, Routing			
Characteristics:	Cable management system with Support and connection accessories			
	Rigid, Plastic conduits			
	Durable - Insulated			
	Non Flame propagating - Self Extinguishing			
UV Resistant	In case of fire they don't release Halogen acids :			
	Chlorine, Fluorine, Bromine, Iodine, Astatine			
Structural material	Modified Thermoplastic Polyolefin			
Classif. EN 61386-1	3 4 4 3			
Compression Resistance	3	Compression Force	>750N / 5cm	
Impact Resistance	4	Mass	2.0 kg	Height 300mm
Temperature Range	4	Lower Temperature Range	- 25 °C	
	3	Higher Temperature Range	+ 105 °C	
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance >100MΩ
Color	Black		Length	3m

TYPE:	16	20	25	32
CODE:	30-21130-016	30-21131-020	30-21132-025	30-21133-032
D₁ OUT.d Ø / mm	16	20	25	32
D₂ IN.d Ø / mm	15,5	16,9	21,4	27,7
Packing / m	150	150	75	75

