
















DOMO SPIRAL - ECO MEDIUM TYPE 750N



TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU			            	
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems				
RoHS Compliant	2022/95/EC Περιορισμός Επικίνδυνων Ουσιών, RoHS				
ECO Solution	With a low environmental footprint contributing to the reduction of CO2 and the consumption of fossil fuels.				
Applications Installations	Outdoor - Indoor				
	Residential, Industrial, Professional Electrical Installations				
	Exposed - Wall Mounted – In floor – In Concrete – On Wood				
Characteristics:	Contribute to reducing the environmental footprint of constructions				
	Pliable, Corrugated – Spiral				
	Cables protection, Management, Routing				
	Non Flame propagating - Self Extinguishing - (FR-SE)				
Structural material	Cable management system with Support and connection accessories				
	UV Resistant				
Classification EN 61386-1	3 3 4 1				
Compression Resist.	3	Compression Force	750N / 5cm		
Impact Resistance	3	Mass	2.0 kg	Height	100mm
Temperature Range	4	Lower Temperature range	- 25 °C		
	1	Higher Temperature range	+ 60 °C		
Bending Resistance	2	Pliable			
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ	
Color	Black				

TYPE:	16	20	25	32	40	50	
CODE:	31-211	00-016	01-020	02-025	03-032	04-040	05-050
D ₁ External Ø / mm	16	20	25	32	40	50	
D ₂ Internal Ø / mm	11	15	19	25	31,5	40	
Packing – Coil / m	100	100	75	50	25	25	

