

## DOMO SPIRAL MEDIUM TYPE 750N



### TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU				
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems				
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS				
Applications	Indoor	Outdoor	Residential	Industrial	
Installations	Cable routing Exposed - Wall Mounted – In floor – In Concrete – On Wood Wiring - Power – Lighting – Automation				
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories UV Resistant				
Structural material	Polyvinyl chloride (U-PVC)				
Classification EN 61386-1	<b>3 3 4 1</b>				
Compression resistance	<b>3</b>	Compression Force		750N / 5cm	
Impact Resistance	<b>3</b>	Mass	2.0 kg	Height	100mm
Temperature Range	<b>4</b>	Lower Temperature range		- 25 °C	
	<b>1</b>	Higher Temperature range		+ 60 °C	
Bending Resistance	<b>2</b>	Pliable			
Electrical Properties	Dielectric Strength		2kv/15min	Insulation Resistance >100MΩ	
Color	Grey - RAL 7035				



<b>TYPE:</b>	<b>16</b>	<b>20</b>	<b>25</b>	<b>32</b>	<b>40</b>	<b>50</b>
<b>CODE:</b>	<b>31-210 01-016</b>	<b>31-210 02-020</b>	<b>31-210 03-025</b>	<b>31-210 04-032</b>	<b>31-210 05-040</b>	<b>31-210 06-050</b>
<b>D<sub>1</sub></b> External Ø / mm	16	20	25	32	40	50
<b>D<sub>2</sub></b> Internal Ø / mm	11	15	19	25	31,5	40
Packing – Coil / m	50	50	50	50	25	25

