
















## HALOGEN FREE CONDUITS

### SPIRAL HF LIGHT TYPE 320N

#### TECHNICAL DATA SHEET

Reference:	LVD 2014/35/EU			            	
Directives & Standards:	EN 61386-1:2008 Cable Management, General Requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems				
Halogen Acid Gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014				
Applications	Indoor Residential and Industrial Installations				
Installations	Cable Routing Flush Installations				
Characteristics	Pliable, Corrugated – Spiral Cable Management Connection and Mounting Accessories available				
Material	Modified Thermoplastic Polyolefin				
Classification: EN 61386-1	<b>2 3 3 2</b>				
Compression Resistance	<b>2</b>	Compression Force	320N / 5cm		
Impact Resistance	<b>3</b>	Mass	1.0 kg	Height	200mm
Temperature Range:	<b>3</b>	Lower Temperature	- 15 °C		
	<b>2</b>	Higher Temperature	+ 90 °C		
Electrical Properties:	Dielectric Strength	2kv/15min	Insulation Resistance	>100MΩ	
Color	Standard	Gray RAL 7035	Other colors available on request		

TYPE:	16	20	25	32	40	50
CODE:	07-210 07-016	07-210 08-020	07-210 09-025	07-210 10-032	07-210 11-040	07-210 12-050
D <sub>1</sub> OD Ø / mm	16	20	25	32	40	50
D <sub>2</sub> ID Ø / mm	10,7	14,5	19	24,3	31,2	39,6
Packing – Coil / m	100	100	50	50	25	25

