



TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU			
Standards	EN 61386-1:2008 Cable Management, General requirements			
Amends	EN 61386-24:2010 Conduit systems buried underground			
Halogen acid gas Amount	DIN EN 60754-1 (VDE 0482-754-1) : 2015-08 EN 60754-1:2014			
Description	Plastic Conduit, Pliable / Corrugated			
Applications	Underground - Outdoor			
Installations	Cable Protection, Routing Management - Buried underground			
	Infrastructures, Road Lighting, Power, Telecom, R.E.S			
Structural material	Modified Thermoplastic Polyolefin			
Characteristics	Resistance - Compression	> 750N		
	Resistance - Impact	N	20 Joule	
	Resistance - UV	R		
	Resistance - Chemicals	R		
	Bending Rdius - Min	10 x Ø OD		
	Temperature Range	Min	-25 °C	
		Max	+60 °C	
Color	Black			



TYPE:	25	32	40	50	60
CODE:	05-21007-025	05-21008-032	05-21009-040	05-21010-050	05-21011-060
D ₁ ODØ / mm	25	32	40	50	60
D ₂ IDØ / mm	19	24	31	39	50
Packing / m	50	50	25	25	25

