

FORTE SPIRAL HEAVY TYPE 1250N



TECHNICAL DATA SHEET

Reference	Low Voltage Directive LVD 2014/35/EU		
Standards	EN 61386-1:2008 Cable Management, General requirements EN 61386-22:2004 + A11:2010 Pliable Conduit Systems		
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS		
Applications Installations	Indoor	Outdoor	Residential Industrial
Characteristics	Pliable, Corrugated – Spiral Non Flame propagating - Self Extinguishing Cable management system with Support and connection accessories UV Resistant		
Structural material	Polyvinyl chloride (U-PVC)		
Classification EN 61386-1	4 4 4 1		
Compression resistance	4	Compression Force	1250N / 5cm
Impact Resistance	4	Mass	2.0 kg
Temperature Range	4	Lower Temperature	- 25 °C
	1	Higher Temperature	+ 60 °C
Bending Resistance	2	Pliable	
Electrical Properties	Dielectric Strength	2kv/15min	Insulation Resistance >100MΩ
Color	Grey - RAL 7035		



TYPE:	16	20	25	32	40	50
CODE:	31-210 07-016	31-210 08-020	31-210 09-025	31-210 10-032	31-210 11-040	31-210 12-050
D ₁ External Ø / mm	16	20	25	32	40	50
D ₂ Internal Ø / mm	11	15	19	25	31,5	40
Packing – Coil / m	50	50	50	25	25	25

