



WATERTIGHT JUNCTION BOXES

SCREWED LID – IP55

190x145

TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU				
Standards Amends	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements EN 60529 Degrees of Protection , Enclosures, IP Rate				
Halogen Free	Techno polymer material Halogen free - EN 60754-2 :2014+A1: 2020				
Applications	Indoor – Outdoor - Residential – Industrial Plastic box with Hinged Screwed Lid Wiring, Junction or Extension – General Proposes With Knock Out entries for Accessories - Conduits – Cables, etc				
Installations	Exposed – Wall mounted				
	Wiring, Power, Lighting, Automation, Telecom, CCTV				
Material	Modified Technopolymer				
Characteristics	IP Rate	Solid	5	Water	5
	Glow Wire Test	650 °C			
	Resistance - UV	LR			
	Resistance - Chemicals	R			
	Resistance - Impact	R			
	Dielectric Strength	+400V			
	Temperature range	-25 °C		+60 °C	
	Color.1	Grey RAL7035			



HF Halogen FREE



IP55



TYPE	190x145
CODE	32-21008-190
A_mm	190
B_mm	145
C_mm	70
D_Pipe OD Ø_mm	16-20-25
E_Entries - Max OD Ø_mm	37
PACKING / pcs	24

