



# WATERTIGHT JUNCTION BOXES

**SCREWED LID & KNOCK OUTS – IP65**
**190x145**

## TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU				
Standards Amends	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements EN 60529 Degrees of Protection , Enclosures, IP Rate				
Halogen Free	Techno polymer material Halogen free - EN 60754-2 :2014+A1: 2020				
Applications	Indoor – Outdoor - Residential – Industrial Plastic box with Hinged Screwed Lid Wiring, Junction or Extension – General Proposes With Knock Out entries for Accessories - Conduits – Cables, etc				
Installations	Exposed – Wall mounted				
	Wiring, Power, Lighting, Automation, Telecom, CCTV				
Material	Modified Technopolymer				
Characteristics	IP Rate	Solid	6	Water	5
	Glow Wire Test	650 °C			
	Resistance - UV	LR			
	Resistance - Chemicals	R			
	Resistance - Impact	R			
	Dielectric Strength	+400V			
	Temperature range	-25 °C		+60 °C	
	Color.1	Grey RAL7035			



<b>TYPE</b>	<b>190x145</b>
<b>CODE</b>	32-21044-190
<b>Lid Screws</b>	Plastic
<b>A _mm</b>	190
<b>B _mm</b>	145
<b>C / mm</b>	70
<b>D Entries - Max OD Ø _mm</b>	32
<b>PACKING / pcs</b>	24

