



SPECIAL FLEXIBLE CONDUITS

COURFLEX® CLIMA

TECHNICAL DATA SHEET

RoHS Compliant:	2022/95/EC Restriction of Hazardous Substances, RoHS			
Applications	Indoor	Outdoor	Residential	Industrial
	Air Condition Drainage			
Installations	Conjunction and Sealing with connectors to terminating devices			
	Exposed - Wall Mounted – On floor – On Wood - Underground			
Characteristics:	Plastic, Flexible, Sheath Spiraled Conduit			
	Profile of P-PVC, Reinforced with Spiral of U-PVC			
	Non Flame propagating - Self Extinguishing			
	Bending Radius: 10 x Ø OD			
Structural Materials:	UV Resistant			
	Profile of P-PVC, Reinforced with Spiral of U-PVC (Polyvinyl Chloride)			
Temperature Range:	+5 °C			
	+ 60 °C			
Color :	White (RAL 9010)			



TYPE:	12	14	16	18	20	22	25
CODE:	16-210 48-012	16-210 49-014	16-210 50-016	16-210 51-018	16-210 52-020	16-210 53-022	16-210 55-025
D ₁ OD Ø / mm	13,3	16	20	21,2	22,5	25,3	28,1
D ₂ ID Ø / mm	12	14	16	18	20	22	25
COIL / m	30	30	30	30	30	30	30

